

Do's and Don'ts of Pneumatic Tool Use Aerosmith Fastening Systems “CT” Tools January 2022

Do's and Don'ts for CT Tools:

1. Oil tool daily according to Aerosmith published recommendations.:
2. Inspect magazine for damage.
3. Inspect tip assembly:
 - a. For damage
 - b. Confirm retaining clip is secure
4. Optimized operation
 - a. Use 3/8" air fitting
 - b. Use 3/8" ID (Internal Diameter) Hose
 - c. Use compressor with:
 - i. Minimum 9-gallon capacity
 - ii. Minimum 6 CFM @ 120 PSI
 - iii. Normal operating pressure 120psi to 140psi.
 - iv. Max Pressure no more than 170psi.
5. Clearing the Occasional “Jam” of a ‘CT’ Tool:
 - a. Always disconnect tool power source (air, battery) prior to cleaning any jammed tools
 - b. If available, always use trigger locks
 - c. Remove all fasteners from tool feed and magazine
 - d. Use the right tool for the right job (e.g.- proper fitting wrenches, screw drivers, etc.)
 - e. Re-assemble with clean parts & seals
6. Proper storage of tool when not in use
 - a. Always remove all fasteners from tool during storage
 - b. Apply trigger lock
 - c. Oil the tool.

