



Recommended Pins and Attachments for HN120

Applications	Recommended Pins					ICC/ES Approval	Attachment Used
		Recommended Pins	Length	Shank	Shank Dia.		
Drywall track to Concrete 	Drywall Track						Attachment A Attachment C
		5323HP	1-1/4"	Smooth	.145	ESR-1799 RR22668	
Wood to Concrete (Subfloor to Concrete) 	Thickness of Wood	Recommended Pins	Length	Shank	Shank Dia.		Attachment B
	1/2"	5323HP	1-1/4"	Smooth	.145	ESR-1799 RR22668	
	3/4"	5323HP	1-1/4"	Smooth	.145	ESR-1799 RR22668	
	1"	5383HP	1-1/2"	Smooth	.145	ESR-1799 RR22668	
	1-1/2"	5573HP	2-1/4"	Smooth	.145	ESR-1799 RR22668	
Wood to Steel Thickness of Steel is 1/8" to 3/16" (Flooring to Steel Frame, Modular Buildings, Truck and Trailer Flooring)	Thickness of Wood	Recommended Pins	Length	Shank	Shank Dia.		Attachment B
	1/2"	5323HP	1-1/4"	Smooth	.145	ESR-1799 RR22668	
	3/4"	5383HP	1-1/2"	Smooth	.145	ESR-1799 RR22668	
	1"	5454HP	1-3/4"	Helical	.145	ESR-1799 RR22668	
	1-1/2"	5573HP	2-1/4"	Smooth	.145	ESR-1799 RR22668	
	1-1/2" ACQ	5573HPG	2-14"	Smooth PT2000	.145	ESR-1799 RR22668	

Attachment for Track to Concrete

Attachment A
For narrow track



Attachment C
High Durability Attachment



Attachment for Wood to Concrete

Attachment B

