



GT38-60LI EXIF

INSULATION FASTENING SYSTEMS

**LITHIUM ION
BATTERY POWERED**

APPLICATIONS

Rigid Insulation to:
Concrete
Concrete Block-CMU
Light Gauge Steel

FEATURES

High Performance Gas
Powered Tools
Lithium Ion Battery Technology
Quick Release Barrel
Drives 1"-6" Plastic Washers

BENEFITS

8,000 Shots per Fully Charged
Battery
1 Hour Battery Recharge Time
Fuel Cell Delivers 1,000 shots
No License Required



The NEW **GT38LI EXIF** and **GT60LI EXIF** gas tools are the perfect compliment to Aerosmith's long line of fastening products.



*With over 50 years in the industry,
Aerosmith is a trusted leader providing
more solutions to contractors.*

CONCRETE INSULATION ANCHOR

White Washer - Fuel purchased separately

P/N	TOOL GROUP	HEAD DIAMETER	ANCHOR LENGTH	PRIMARY APPLICATIONS	QTY
GT100ICBB	GT38-60EXIF	60 mm	1"	Rigid Insulation To Concrete	1200
GT112ICBB	GT38-60EXIF	60 mm	1-1/2"	Rigid Insulation To Concrete	1100
GT200ICBB	GT38-60EXIF	60 mm	2"	Rigid Insulation To Concrete	950
GT212ICBB	GT38-60EXIF	60 mm	2-1/2"	Rigid Insulation To Concrete	880
GT300ICBB	GT38-60EXIF	60 mm	3"	Rigid Insulation To Concrete	760
GT312ICBB	GT38-60EXIF	60 mm	3-1/2"	Rigid Insulation To Concrete	660
GT400ICBB	GT38-60EXIF	60 mm	4"	Rigid Insulation To Concrete	580
GT500ICBB	GT38-60EXIF	60 mm	5"	Rigid Insulation To Concrete	480
GT600ICBB	GT38-60EXIF	60 mm	6"	Rigid Insulation To Concrete	400

LIGHT GAUGE STEEL INSULATION ANCHOR

Gray Washer - Fuel purchased separately

P/N	TOOL GROUP	HEAD DIAMETER	ANCHOR LENGTH	PRIMARY APPLICATIONS	QTY
GT100ISBB	GT38-60 EXIF	60 mm	1"	Rigid Insulation To LGS/CFS	1200
GT112ISBB	GT38-60 EXIF	60 mm	1-1/2"	Rigid Insulation To LGS/CFS	1100
GT200ISBB	GT38-60 EXIF	60 mm	2"	Rigid Insulation To LGS/CFS	950
GT212ISBB	GT38-60 EXIF	60 mm	2-1/2"	Rigid Insulation To LGS/CFS	880
GT300ISBB	GT38-60 EXIF	60 mm	3"	Rigid Insulation To LGS/CFS	760

AC70 FASTENER TESTING 4000psi AND 6000psi CONCRETE

P/N	MIN. CONCRETE COMPRESSIVE STRENGTH (psi)	MIN DISTANCE EDGE (in)	AVERAGE EMBED DEPTH (in)	TENSION LOAD (IBF)
GTXXXIC ²	4000	3"	7/8"	53
GTXXXIC ²	6000	3"	7/8"	167

ULTIMATE TENSION LOAD VALUES AEROSMITH EXIF PIN INTO 16 GAUGE (54 MIL) STEEL

PIN TYPE	AVERAGE ULTIMATE TENSION LOAD VALUE LBS./FT2
Aerosmith EXIF Knurled Pin 151	151
Aerosmith	GT60LI EXIF

INSULATION TOOLS, FUEL AND ACCESSORIES

ITEM #	DISCRIPTION
GT38LI EXIF	Lithium GasTool
GT60LI EXIF	Lithium Gas Tool
GTFUEL2	2 pack - Fuel Cell
GTFUEL12	12 pack - Fuel Cell

¹ - Allowable Capacity is based on the calculations found in Section 3.2.4 of AC70 and are defined on the summary page of this report.

² XXX denotes numbers used in fastener description to represent nominal fastener length