

PR-10M 2-Way Radio

NEW

VHF MURS & Analog
License-Free Business Band
Portable Radio

COMPACT, LIGHT
TO CARRY



PR-10M VHF MURS

Features

- Rugged & Reliable
- Powerful 2-Watt Transmitter
- PC Programmable
 - *FREE Software Download & PURCHASE of Optional Programming Cable - #60201138
- 16 Channel Capacity, 7 MURS Simplex Frequencies
- Signaling: CTCSS/DCSS Encode/Decode
- Channel Number Voice Prompt
- Small Size: 4.75" H x 2" W x 1.25" D
- Weight w/ Battery: 9.5 oz
- Battery Life: 14 Hours
- 2000mAH/14.8 Wh, Li-Poly Battery Pack
- 1-Watt, Loud, Easy-to-Hear Audio Output
- 2-Pin Audio Accessory Connector
- 1 Year Warranty
- Requires Programmer:
 - 3 Programmable Function Buttons (PFB)
 - Channel Scan Capable
 - VOX Hands-Free Capable

NOTE: PR-10M NOT capable of selective signaling (i.e. 2-tone encode or DTMF encode capability)

Each PR-10M Radio Includes:

- Antenna
- 2000mA Battery Pack (14 Hour Duty)
- Spring-Action Belt Clip
- Drop-in 3Hr Charge Tray w/ 110-220VAC Adapter



*Optional
Programming
Cable (#60201138)

RITRON[®]

Factory Programmed Default Settings - 7 MURS Frequencies

| Ch. # | Freq. Code | Tone Code/Freq. | Bandwidth |
|-------|---------------|-----------------|------------------|
| Ch 1 | #19 - 151.820 | #4 - 77Hz | Narrow - 12.5KHz |
| Ch 2 | #20 - 151.880 | #4 - 77Hz | Narrow - 12.5KHz |
| Ch 3 | #21 - 151.940 | #4 - 77Hz | Narrow - 12.5KHz |
| Ch 4 | #23 - 154.570 | #4 - 77Hz | Narrow - 12.5KHz |
| Ch 5 | #22 - 154.600 | #4 - 77Hz | Narrow - 12.5KHz |
| Ch 6 | #01 - 154.600 | #4 - 77Hz | Wide - 25KHz |
| Ch 7 | #02 - 154.570 | #4 - 77Hz | Wide - 25KHz |

Radio Specifications:

| Model: PR-10M | PR-10M VHF MURS, Analog LICENSE-FREE Business Band Portable 2-Way Radio |
|-------------------------------|---|
| Channels | 16 Channels MAX, 2 Zones, 16 Channels Per Zone |
| Operating Temperature | -25C to +60C |
| Battery Life | 14 Hours Analog |
| Dimensions | 4.75" H x 2" W x 1.25" D |
| Weight | Weight w/ Battery: 9.5 oz |
| Signaling | Analog: CTCSS/DCS |
| Programmable Function Buttons | 3 |
| Transmitter TX Power | 2-Watt |
| Receiver Sensitivity | Analog: .22uV / -120dBm (12dB SINAD) |
| Audio Output Power | Loud, 1-Watt Audio |
| Regulatory Approvals | FCC-PART-95 |



Each Radio Includes:
Flex Antenna,
Spring-Action Belt Clip,
Rechargeable Battery,
Drop-In Charger Stand
and 110-220V AC
Adapter.



6 Unit Charger Kit

Kit includes base mounting plate, 6 plug pigtail cable, (6) adapters and 110-220V AC Adapter. Kit does not include 6 individual radio charging stands shown in image. Charging stands come standard with each PR series radio. Dimensions: 11"W x 7"L x 4"H. **Assembly Required.**



Remote Speaker Mic
RSM-10X



Ear Hook Earset
RHD-16X

Other Compatible VHF MURS Products Made In USA Products

LoudMouth Wireless PA
LM-600Analog



Radio-To-Intercom Bridge
RIB-600Analog



Desk Top Base Station
PBS-147M



Q Series Callbox Fixed
location 2-way Radio.
RQX-117M
RQX-111M

