



Quick Assist[®]

Wireless Shopper Callbox



- Works With Existing 2-Way Radios
- Improve Loss Prevention
- Improve Staff Productivity
- Increase Customer Service



Benefits:

- Works with existing store 2-way radios
- Virtually eliminates in-store PA paging
- Improves employee efficiency, reduces payroll costs
- Simple to install and maintain by store personnel – can be relocated to different locations
- Provides Approx 75,000* Sq. Ft of Coverage

*range may be less due to obstructions.

Features:

- Works independently of any network, does not use Wifi or IP connection
- Transmits message instantly and directly to store 2-way radios
- Battery powered, no wiring required
- Large easy-to-see signage
- Recordable voice messages
- Durable, water-resistant
- Designed and Made In The USA



For more information, contact us at:
800-872-1872

Made For Retail Applications...

Locked Cabinet Areas • Seasonal Areas • Heavy Merchandise • Fitting Rooms • Customer Pick-Up • Delivery/Receiving Docks



Quick Assist® Enhances The Shopping Experience And Controls Costs...



- Built-In Mounting Flanges
- Message Transmission Confirmation Light
- Sealed, Polycarbonate, Water-Resistant Housing
- Internal, No Tamper Antenna
- Bold Design and Messaging
- Large, Easy-to-Use Call Button



Radio Compatibility!

The Ritron Quick Assist callbox is available in the VHF MURS License-Free Business Band, and the licensed VHF and UHF Business Band. The appropriate Quick Assist callbox is compatible with virtually any other business band two-way radio operating on the same VHF or UHF frequencies.

MODELS	VHF		VHF		UHF	
	RQA-151 M	RQA-152M	RQA-151	RQA-152	RQA-451	RQA-452
Transmit Power:	120mW	1 Watt	120mW	1 Watt	120mW	1Watt
	MURS License-Free		Licensed Frequencies		Licensed Frequencies	
FCC Rule Parts:	95J		90		90	
Frequency Range:	150 to 165 MHz 5 MURS frequencies below 151.880, 151.940, 154.600, 154.570, 151.280		150 – 165 MHz Narrow Band		450 – 470 MHz Narrow Band	
ALL MODELS						
Coded Signaling:	Encode CTCSS, DCS, DTMF, 3-7 tone SelCall					
Typical Range/Coverage:	One-half mile, line-of-sight to a portable 2-way radio, or approximately 75,000 sq. ft. Greater range is possible when a radio repeater is used.					
Battery Life:	1 year when using AA Alkaline, non-rechargeable batteries or approximately 7,000 transmissions.					
Internal Battery:	6 AA Alkaline, non-rechargeable batteries.					
Antenna:	Internal, tamper-proof, ¼ wave					
Housing:	Gasketed, water-resistant, polycarbonate with UV stabilizer for outdoor use.					
Dimensions:	7.57" x 5.07" x 2.1" (19.23cm x 12.88cm x 5.33cm)					
Weight:	1 pound, without batteries					
Switch Input:	Front-panel, momentary push button					
Voice Message "Assistance Needed"	Customizable, 12 seconds max, if Reset Message also used.					
Voice Message "Reset"	Optional, Customizable, 12 seconds max					
Voice Message "Low Battery Alert"	Customizable - 2 seconds					
Voice Message "External Power Fail"	Customizable - 2 seconds					
Programming Method:	User Programmable with PC Programmer and USB to 5 Pin Mini USB Cable					
Programmable Features:	<ul style="list-style-type: none"> - TX audio companding (allows compatibility with certain 2-way radios) - Repeat Transmission Schedules - Voice message recording via on-board microphone or pre-recorded .wav file - Front panel TX indicator LED - Can be programmed for use with radio repeaters 					

Fixed Location Intercom

Fixed location AC powered base station radio. Eliminate the recurring costs of lost, damaged or stolen portable radios with a desk top or wall-mounted base station radio.

About Ritron Inc.
 Founded in 1977, Ritron, Inc., is a U.S. company specializing in the design and manufacture of RF wireless voice and data communication products. It offers wireless solutions for commercial, industrial, military, OEM and integrator markets.

Call 800-USA-1-USA (872-1872) or email us at ritron@ritron.com

